



Battery Voltage Protector **BGW Series**

Model **BGW-200** 200 Amps

Design Features

- Waterproof
- Prevents excessive discharge of batteries
- Can be set to connect / disconnect at several different voltages
- Prevents damage to connected components
- Protects against excessive voltage caused by faulty alternators or chargers







MODEL NO.	BGW-200
MAXIMUM CONTINUOUS LOAD CURRENT (SHUTDOWN CURRENT)	200A
PEAK CURRENT	1200A (±0.7 sec)
OPERATING VOLTAGE	Autodetect 12 or 24VDC 6-19 VDC (12VDC) ; 20-35 VDC (24VDC) 10 programmable voltage thresholds
CURRENT CONSUMPTION	3.2mA
CURRENT CONSUMPTION IN OFF POSITION OR UNDER- OR OVER- VOLTAGE POSITION	3.2mA
VOLTAGE DROP	50 mV @ 200A
SHUTDOWN PROTECTION	Low Voltage, Overvoltage, Over Current, Temperature
CONNECTIONS	Remote On/Off Switch Status / Alarm connection for user provided device such as buzzer, lamp, or relay.
CURRENT ACCURACY	10%
VOLTAGE ACCURACY	2%
CASEWORK	Rubberized Polyurethane PU552
ENCLOSURE TYPE	IP66 (Waterproof)
SAFETY & EMC	EMISSION - EN 61000-6-3:2007 IMMUNITY - EN 61000-6-2:2005 CE, UKCA, RoHS
DIMENSIONS, MM (D \times W \times H), MM	76 x 111 x 39
DIMENSIONS, INCHES (D x W x H), INCH	2.99 x 4.37 x 1.53
WEIGHT, KG	0.29
WEIGHT, LB	0.65

NOTE: Specifications are subject to change without notice