

## MS-PAE SERIES | 120/240V INVERTER/CHARGER

### Introduction

The MS-PAE 120/240V Series Inverter/Charger is a pure sine wave inverter designed specifically for the most demanding renewable energy applications. The MS-PAE Series is powerful, easy-to-use, and best of all, cost effective.

No series stacking required: The unique design of the MS-PAE Series can provide 120 and 240 volts output in one unit, eliminating the need to stack two units together to get 240 volts.

Parallel stacking: You can parallel up to four inverter/chargers for up to 17.6 kW of power at 120/240V. MP Panels and Router are required for parallel stacking the MS-PAE Series.

Power Factor Corrected (PFC) Charger: Our PFC charger is built into all of our inverter chargers. It uses less energy from a generator than a standard charger – 25-30% less AC current than standard chargers.



### Features

- Pure sine wave – Power your TVs, computers and other sensitive electronics without worry. The pure sine wave inverter and power factor corrected charger provide clean, reliable inverter power with low total harmonic distortion (THD) of less than 5%.
- Choices – The MS-PAE Series comes in 24 and 48 volt configurations, allowing you to choose the model that is right for you.
- Versatile mounting – Mount the MS-PAE Series on a shelf or wall.
- Lightweight – The lightweight aluminum base and cover also provides noise reduction and corrosion resistance.
- Multiple ports – The MS-PAE Series provides multiple ports, including an RS485 communication port for network expansion, and a remote port.
- Accessible design – The extra large AC access cover with terminal screw block and 360° DC connection terminals with covers make this inverter more accessible when it needs to be.
- Convenient switches – The MS-PAE Series comes with an on/off inverter-mounted switch with an easy-to-read LED indicator.

### Model Numbers

- MS4024PAE
- MS4448PAE

### Available For

- Renewable Energy Systems
- Off-grid Power
- Back-up Power

### Available Accessories

- Auto Generator Start - ME-AGS-N
- Battery Monitor Kit
- Conduit Box
- Fuse Blocks
- Remote - ME-ARC
- Remote - ME-RC
- Router - ME-ARTR
- MP and MMP Panels



Pure Sine Wave



24,48

Battery Voltage Options



4000-4400 VA

Continuous Output Options



# SPECIFICATIONS

	MS4024PAE	MS4448PAE
<b>INVERTER SPECIFICATIONS</b>		
<b>Input battery voltage range</b>	18 - 34 VDC	36 - 64 VDC
<b>Nominal AC output voltage</b>	120/240 VAC split phase ( $\pm 5\%$ )	120/240 VAC split phase ( $\pm 5\%$ )
<b>Output frequency and accuracy</b>	60 Hz $\pm 0.1$ Hz	60 Hz $\pm 0.1$ Hz
<b>Total Harmonic Distortion (THD)</b>	< 5%	< 5%
<b>1 msec surge current (amps AC)</b>	Line-Neutral: 120, Line-Line: 70	Line-Neutral: 120, Line-Line: 70
<b>100 msec surge current (amps AC)</b>	Line-Neutral: 72, Line-Line: 40	Line-Neutral: 75, Line-Line: 40
<b>5 sec surge power (real watts)</b>	5800	8500
<b>30 sec surge power (real watts)</b>	5200	6000
<b>5 min surge power (real watts)</b>	4800	5400
<b>30 min surge power (real watts)</b>	4500	4800
<b>Continuous power output at 25° C</b>	4000 VA (L-L)	4400 VA (L-L)
<b>Maximum continuous input current</b>	266 ADC	144 ADC
<b>Inverter efficiency (peak)</b>	93%	94%
<b>Transfer time</b>	16 msec	16 msec
<b>Search mode (typical)</b>	< 6 watts	< 6 watts
<b>No load (120 VAC output, typical)</b>	27 watts	25 watts
<b>Waveform</b>	Pure Sine Wave	Pure Sine Wave
<b>CHARGER SPECIFICATIONS</b>		
<b>Continuous output at 25° C</b>	105 ADC	60 ADC
<b>Charger efficiency</b>	85%	85%
<b>Power factor</b>	> .95	> .95
<b>Input current at rated output (AC amps)</b>	15 AAC per leg at 120/240 VAC split phase	17.5 AAC per leg at 120/240 VAC split phase
<b>GENERAL FEATURES AND CAPABILITIES</b>		
<b>Transfer relay capability</b>	2 legs at 30A per leg transfer standard on all models	
<b>Five stage charging capability</b>	Bulk, Absorb, Float, Equalize (requires remote), and Battery Saver™	
<b>Battery temperature compensation</b>	Yes, 15 ft Battery Temp Sensor standard	
<b>Internal cooling</b>	0 to 120 cfm variable speed drive using dual 92mm brushless DC fans	
<b>Overcurrent protection</b>	Yes, with two overlapping circuits	
<b>Overtemperature protection</b>	Yes on transformer, MOSFETS, and battery	
<b>Corrosion protection</b>	Yes, PCB's conformal coated, powder coated chassis/top, and stainless steel fasteners	
<b>Listings</b>	ETL Listed to ANSI / UL1741 and CSA STD C22.2 No.107.1-01	
<b>Warranty</b>	Three years parts and labor (five years when installed on MMP or MP system)	

PHYSICAL SPECIFICATIONS		
Dimensions (l x w x h)	13.75" x 12.65" x 8.0" (34.9 cm x 32.1 cm x 20.3 cm)	
Mounting	Shelf, wall (no vents on bottom), MP or MMP panels	
Weight	55 lb (24.9 kg)	55 lb (24.9 kg)
Shipping weight	62 lb (28.2 kg)	63 lb (29.6 kg)
Max operating altitude	15,000' (4570 m)	
Temperature (Operating/Non-operating)	-20° C to +60° C (-4° F to 140° F) to -40° C to +70° C (-40° F to 158° F)	
Operating humidity	0 to 95% RH non-condensing	



## GENERAL NOTES

Testing for specifications at 25°C.  
Specifications subject to change without notice.



## AGENCY APPROVALS & CERTIFICATIONS

- Safe and reliable: The MS-PAE Series is ETL Listed to the stringent requirements of UL 1741 and CSA C22.2 #107.1-01 for renewable energy installations.

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com) SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

## CONTACT US

651-653-7000  
800-553-6418  
[InverterInfo@sensata.com](mailto:InverterInfo@sensata.com)

**Power Conversion**  
[www.magnum-dimensions.com](http://www.magnum-dimensions.com)