



samlexamerica®

DC-AC Inverter Pure Sine Wave

Model

PST-1500-12
12 VDC - 120 VAC

PST-1500-24
24 VDC - 120 VAC

PST-1500-48
48 VDC - 120 VAC

Design Features

- Pure sine wave output with <3% THD for sensitive electronics and motor-driven loads
- High efficiency with ultra-low idle current for extended runtime
- 3000 W surge power for reliable startup of demanding loads
- Hardwire-ready with dual GFCI-protected AC outlets
- Optional remote control with ignition-controlled ON/OFF capability
- Universal Protection Circuit (UPC) and temperature-controlled cooling fan for dependable mobile power

3 YEAR LIMITED WARRANTY



MODEL NO.		PST-1500-12	PST-1500-24	PST-1500-48
OUTPUT	OUTPUT VOLTAGE	120 VAC $\pm$ 3%		
	MAXIMUM OUTPUT CURRENT	16.7 A		
	OUTPUT FREQUENCY	60 Hz $\pm$ 1%		
	TYPE OF OUTPUT WAVEFORM	Pure Sine Wave		
	TOTAL HARMONIC DISTORTION OF OUTPUT WAVEFORM	< 3%		
	CONTINUOUS OUTPUT POWER (At Power Factor = 1)	1500 Watts		
	SURGE OUTPUT POWER	3000 Watts		
INPUT	PEAK EFFICIENCY	> 85%	> 88%	> 90%
	AC OUTPUT CONNECTIONS	(i) NEMA5-20R GFCI Duplex Receptacle (ii) Terminal block for hardwiring: Hole diameter (4 mm / 0.16") and Set Screw (#6 x 40TPI or M3.5 x 0.6 mm Pitch)		
	NOMINAL DC INPUT VOLTAGE	12 V	24 V	48 V
	DC INPUT VOLTAGE RANGE	10.7 - 16.5 VDC	21.4 - 33 VDC	42.0 - 60.0 VDC
	MAXIMUM INPUT CURRENT	200 A	100 A	50 A
	DC INPUT CURRENT AT NO LOAD	< 1.0 A	< 0.8 A	< 0.5 A
	DC INPUT CONNECTIONS	Bolt & Nut: 5/16" x 18 TPI		
DISPLAY	DC INPUT FUSES (INTERNAL) (Automotive, Blade Type)	5 x 40 A = 200 A (Each 40 A, 32 V)	5 x 20 A = 100 A (Each 20 A, 32 V)	5 x 10 A = 50 A (Each 10 A, 58 V)
	LED	Power, Overload, Over Temperature		
PROTECTIONS	LOW DC INPUT VOLTAGE ALARM	10.7 V $\pm$ 0.1 V	21.4 V $\pm$ 0.2 V	42 V $\pm$ 0.4 V
	LOW DC INPUT VOLTAGE SHUTDOWN	10 V $\pm$ 0.1 V; Auto-reset: 11.5 V $\pm$ 0.3 V	20 V $\pm$ 0.2 V; Auto-reset: 23 V $\pm$ 0.5 V	40 V $\pm$ 0.4 V; Auto-reset: 46 V $\pm$ 1.0 V
	HIGH DC INPUT VOLTAGE SHUTDOWN	17 V; Auto-reset: < 17 V	34 V; Auto-reset: < 34 V	64 V; Auto-reset: < 64 V
	SHORT CIRCUIT SHUTDOWN	When output voltage drops to 80 V or lower for 1 to 1.5 sec		
	OVERLOAD SHUTDOWN	At overload of 110% to 115% for 2 to 2.5 sec		
	GROUND FAULT SHUTDOWN	Through GFCI outlets (5 to 6 mA leakage)		
	OVER TEMPERATURE SHUTDOWN	90 °C $\pm$ 5 °C / 194 °F $\pm$ 41 °F (Sensed at internal hot spot); Auto reset at 65 °C $\pm$ 5 °C / 149 °F $\pm$ 41 °F		
REMOTE	REVERSE POLARITY ON DC INPUT SIDE	External/internal DC sides fuses will blow		
	WIRED REMOTE CONTROL WITH LED/LED DISPLAY	• RC-300 (Optional, sold separately) with LCD/LED Display, 25' / 7.6 m cable connected through modular jack (10P10C)		
COOLING	WIRED ON/OFF CONTROL	• 2-Wire and 1-Wire On/Off control connected through hard wiring terminal block		
	FORCED AIR COOLING	2 Temperature controlled fans (Temperature is sensed at internal hot spot) Fan ON at 55 °C $\pm$ 3 °C / 131 °F $\pm$ 37.4 °F; Fan OFF at 45 °C $\pm$ 3 °C / 113 °F $\pm$ 37.4 °F		
COMPLIANCE	SAFETY	Intertek - ETL Listed. Conforms to UL Standard 458, and CSA Std. C22.2 No. 107.1		
	EMI/EMC	FCC Part 15(B), Class B		
	HAZARDOUS SUBSTANCE RESTRICTION	RoHS Compliant (Lead Free)		
ENVIRONMENT	OPERATING TEMPERATURE RANGE	-20 to 40 °C / -4 to 104 °F		
	STORAGE TEMPERATURE	-30 to 70 °C / -22 to 158 °F		
	RELATIVE HUMIDITY	90%, non-condensing		
DIMENSIONS	(W X D X H), MM / INCHES	263.0 x 468.2 x 105.6 / 10.35 x 18.43 x 4.16		
WEIGHT	KG / LB	7.1 / 15.6		

NOTES: 1. All power ratings are specified for resistive load at power factor = 1.
2. All specifications given above are at ambient temperature of 25 °C / 77 °F.
3. Specifications are subject to change without notice

12001-PST-1500-12-24-48-0826